



GE  
Lighting

## 71430 - GE CFL Multi-Volt ProLine™ Electronic Program / Rapid Start Ballast

### GEC213-MVPS-3W

- ☞ Multi-Voltage technology means a single ballast handles voltage from 108V to 305V
- ☞ Programmed starting for extended lamp life
- ☞ End-of-Lamp-Life Protection
- ☞ Color Coded Poke-In Connectors simplifies wiring
- ☞ 3-Way Ballast Kit (-3W) includes mounting plate, lead wires, extraction tool and mounting hardware for side exit, bottom exit or bottom exit with studs mounting

### Product Photo



### GENERAL CHARACTERISTICS

Ballast Factor	Normal
Ballast Type	Program / Rapid Start
Case Temperature (Max)	70 °C
Enclosure Type	Metal
Line Voltage Regulation (+/-)	10%
Classification (Regulations)	CSA UL Class P UL Listed UL Type 1 Outdoor UL Type CC UL Type HL FCC Part 18 Class B at 120 volts
Sound Rating	A (20-24 decibels)
Starting Method	Programmed start
Product Technology	Compact Fluorescent Series
Lamp Wiring	Active
Power Factor Correction	

### PRODUCT INFORMATION

Product Code	71430
Description	GEC213-MVPS-3W
Alternative Unit Of Measure	CASE

### DIMENSIONS

Weight	0.56 lb
Exit Type	
Remote Mount Distance	20.0 ft

### Case Dimensions

Length	5.0in
Width	2.4in
Height	1.0in

### Mounting Dimensions

Mount Length	4.63in
--------------	--------

### SAFETY & PERFORMANCE

- ☞ CS\_A
- ☞ UL\_Cls\_P
- ☞ UL\_Listed
- ☞ UL\_Type1\_Out
- ☞ UL\_Type\_CC
- ☞ UL\_Type\_HL
- ☞ FCC\_Part\_18

### CAUTIONS & WARNINGS

#### Warning

Risk of Electric Shock

Properly ground ballast and fixture.

Turn power off before servicing--see instructions.

### SPECIFICATIONS BY LAMP & WATTAGE

Lamp	# of Lamps	Line Volts	System Watts	Nom. Line Current	System Ballast Factor	Ballast Efficacy Factor	Power Factor% (>=)	Crest Factor (<=)	THD% (<=)	Min. Starting Temp (F / C)
CFQ18W	1	277	20	0.07	1.0	5	0.97	1.5	12	-20
CFQ18W	1	120	20	0.17	1.0	5	0.99	1.5	12	-20
CFS16W	1	277	17	0.06	1.0	6	0.96	1.5	12	-20
CFS16W	1	120	17	0.14	1.0	6	0.96	1.5	12	-20
CFTR18W	1	277	20	0.07	1.0	5	0.97	1.5	12	-20
CFTR18W	1	120	20	0.17	1.0	5	0.99	1.5	12	-20
CFQ13W	1	120	16	0.16	1.0	6	0.96	1.5	10	-20

CFQ13W	2	120	29	0.25	1.0	3	0.99	1.5	10	-20
CFQ13W	1	277	16	0.06	1.0	6	0.96	1.5	10	-20
CFQ13W	2	277	29	0.11	1.0	3	0.99	1.5	10	-20
CFS10W	1	120	13	0.11	1.05	8	0.96	1.5	14	-20
CFS10W	1	277	13	0.05	1.05	8	0.96	1.5	14	-20
CFS10W	2	120	23	0.19	0.95	4	0.97	1.5	11	-20
CFTR13W	1	277	16	0.06	1.0	6	0.96	1.5	10	-20
CFTR13W	2	120	29	0.25	1.0	3	0.99	1.5	10	-20
CFS10W	2	277	23	0.09	0.95	4	0.97	1.5	11	-20
CFTR13W	1	120	16	0.16	1.0	6	0.96	1.5	10	-20
CFTR13W	2	277	29	0.11	1.0	3	0.99	1.5	10	-20

Mar 1, 2016 3:05:29 PM For additional information, visit [www.gelighting.com](http://www.gelighting.com)